



DEPTHS AVAILABLE ARE 2" & 4"

**NOTES:**

1. HIGH VELOCITY PLEATS SHALL BE MERV 8 PER ASHRAE 52.2
2. FRAME-HIGH WET STRENGTH 28 POINT BEVERAGE BOARD
3. 100% SYNTHETIC MEDIA
4. SUPPORT GRID-SINGLE DIMENSION EXPANDED METAL BONDED 100% TO MEDIA
5. ADHESIVE-WHITE GLUE UTILIZED TO ATTACH STRAPS TO MEDIA AND MEDIA TO THE FRAME.
6. CLASSIFIED BY UL AS TO FLAMMABILITY ONLY. CLASS 2

EXAMPLE OF MODEL NO. : 85455.022024

\*\*\*\*\* MEDIA SERIES:

85455 - HIGH VELOCITY PLEATED FILTER

MODEL NO.: \_\_\_\_\_ QTY: \_\_\_\_\_  
 MODEL NO.: \_\_\_\_\_ QTY: \_\_\_\_\_  
 MODEL NO.: \_\_\_\_\_ QTY: \_\_\_\_\_

MODEL NUMBER	NOMINAL SIZE	ACTUAL SIZE		MEDIA AREA (SQ. FT.)		RATED CFM	ACTUAL DEPTH	HV PLEAT PD ("w.g.)
		"A"	"B"	2"	4"			
*****, __1224	12 X 24 X D	11 3/8"	23 3/8"	8.7	16.5	1000		
*****, __1620	16 X 20 X D	15 1/2"	19 1/2"	10.0	18.0	1110		
*****, __1625	16 X 25 X D	15 1/2"	24 1/2"	12.4	22.6	1390		
*****, __1824	18 X 24 X D	17 3/8"	23 3/8"	13.8	24.2	1500		
*****, __2020	20 X 20 X D	19 1/2"	19 1/2"	12.4	22.3	1390		
*****, __2024	20 X 24 X D	19 3/8"	23 3/8"	15.3	24.0	1390	1-7/8"	0.29
*****, __2025	20 X 25 X D	19 1/2"	24 1/2"	15.5	27.7	1735	3-7/8"	0.35
*****, __2424	24 X 24 X D	23 3/8"	23 3/8"	17.6	28.8	2000		

TITLE:  
PRE PLEAT HV PRODUCT CLASS



DRAWING NO.  
PP40 HV

